

FEATURES

- Full bore for optimal flow performance with minimal head loss
- Specially compounded nitrile seals designed to exceed valve life
- All plastic design for maximum corrosion resistance
- Integral Purge/Bypass ports for compact and reliable connections
- Open and Close indicators
- Precision manufacturing processes ensure lower operating torques
- ISO 9001 certified manufacturing facility
- Each valve includes a Traceability label



PE Ball Valve with Purge/Bypass connection points

TECHNICAL DATA

Standards:	EN 1555-4, EN 122201-4	
Size Range:	DN 20 – DN 400	Standard 1/4 Turn
	DN 160 – DN400	Gearbox Option 2 ½ Turn
Pressure Rating:	PE100, SDR 11 GAS, WATER PN 16	
Materials:	Polyethylene Body Polypropylene Ball Nitrile Seat and Seals	
Spigot Ends:	Suitable for butt welding and electrofusion welding	
Options:	Stem Extension Gearbox 2 ½ Turn – Short type or Extended type Purge Extensions – Single or Double Bypass Valve arrangement	



PE Ball Valve with Extended Gearbox



PE Ball Valve with Gearbox (Short) and Bypass Valve arrangement

CIVIL PIPE SUPPLIES

ABN 58 196 496 597
2 Potassium St. Narangba Qld 4504
PO Box 304, North Lakes Qld 4509

CONTACT

T: +61 7 3204 8906
E: sales@civilpipes.com.au
W: www.civilpipes.com.au

The products shown form part of our continuous improvement program and as such the product specifications may be changed without notice. All warranties relating to accuracy, completeness, or suitability for any particular purpose and all liability for any loss, damage or costs incurred relating to the use of this information are excluded. © CIVIL PIPE SUPPLIES 2015 All Rights Reserved.



PEBV_0117