

FERRULE COCKS – STANDARD

Standards:	AS/NZS 3718
Size Range:	DN 20 – 50
Pressure Range:	PN 16
Material:	DR Brass
Inlet Range:	F-BSP Tapered
Outlet Options:	Male Union (Ferrule Bend connection), PE Compression



STD FERRULE COCKS

Dia	MU	PE
20	TFC20	TFCP20
25	TFC25	TFCP25
32	TFC32	TFCP32
40	TFC40	TFCP40
50	TFC50	TFCP50

FERRULE COCKS – TPFNR

Standards:	AS/NZS 3718
Size Range:	DN 20 – 50
Pressure Range:	PN 16
Material:	DR Brass
Types:	Bonnet, Capped
Inlet Range:	F-BSP Tapered
Outlet Options:	Male Union (Ferrule Bend connection), PE Compression
Application:	Can be installed under pressure



TPFNR FERRULE COCKS – BONNET

Dia	Bonnet MU	Bonnet PE
20	TFTB20	TFTBP20
25	TFTB25	TFTBP25
32	TFTB32	TFTBP32
40	TFTB40	TFTBP40
50	TFTB50	TFTBP50

TPFNR FERRULE COCKS – CAPPED

Dia	Capped MU	Capped PE
20	TFTC20	TFTCP20
25	TFTC25	TFTCP25
32	TFTC32	TFTCP32
40	TFTC40	TFTCP40
50	TFTC50	TFTCP50

FERRULE BENDS

Standards:	AS 3688
Size Range:	DN 20 – 50
Pressure Range:	PN 16
Material:	DR Brass
Inlet:	Female Union (Ferrule Cock connection)
Outlet Options:	M-BSP Tapered, F-BSP, Copper Capillary



FERRULE BENDS			
Dia	M-BSP	F-BSP	Cu Sol
20	TFBM20	TFBF20	TFBS20
25	TFBM25	TFBF25	TFBS25
32	TFBM32	TFBF32	TFBM32
40	TFBM40	TFBF40	TFBM40
50	TFBM50	TFBF50	TFBM50

DN32 – 50 M-BSP bends also suitable for copper capillary



Ferrule Key (Code – TFK)



Ferrule Bonnet Assembly
c/w Jumper Valve



Ferrule Cap Assembly

FERRULE COCK ACCESSORIES

Dia	Ferrule Bonnet	Ferrule Cap
20	TFBA20	TFTL20
25	TFBA25	TFTL25
32	TFBA32	TFTL32
40	TFBA40	TFTL40
50	TFBA50	TFTL50

CIVILPIPES PTY LTD

ABN 30 168 566 667
2 Potassium St. Narangba Qld 4504
PO Box 304, North Lakes Qld 4509



Web:
civilpipes.com.au



Telephone:
+61 7 3053 3456



E-mail:
sales@civilpipes.com.au

