



APPLICATIONS

- Drain, Waste & Vent Applications
- Gravity Sewer System

FEATURES

- Chemical Resistant
- Corrosion Resistant
- Smooth Bore – Low flow resistance
- Light Weight – Installation savings
- Lead Free

TECHNICAL DATA

Standard:	AS/NZS 1260:2002 Certification No. AMI 1540
Size Range:	DN 100 - 300
Stiffness Range:	SN4, SN6, SN8 & SN10
Lengths:	3m, 6m Spigot-Socket
Joining:	Rubber Ring Joint or Solvent Weld Joint

DWV PIPE – RRJ & SWJ								
DN	OD	Length	Class	Joint	Weight (kg)		Pack Qty	Code
					Length	Pack		
100	110	6 m	SN10	RRJ	8	545	67	PVCDPI0106R
150	160	3 m	SN8 SC	RRJ	9	260	28	PVCDPI5083R
150	160	3 m	SN8 Solid	RRJ	12	330	28	PVCDPI5083RS
225	250	3 m	SN8	RRJ	28	350	12	PVCDP22083R
300	315	3 m	SN8	RRJ	42	270	6	PVCDP30083R
100	110	6 m	SN6 SC	SWJ	7	485	67	PVCDPI0066S
100	110	6 m	SN6 Slotted	SWJ	7	470	67	PVCDPI0066SSL
150	160	6 m	SN4 SC	SWJ	16	535	33	PVCDPI5046S
225	250	6 m	SN4	SWJ	44	540	12	PVCDP22046S
300	315	6 m	SN4	SWJ	71	430	6	PVCDP30046S
100	110	6 m	SN10	SWJ	8	540	67	PVCDPI0106S
150	160	3 m	SN8 SC	SWJ	9	255	28	PVCDPI5083S
225	250	3 m	SN8	SWJ	27	345	12	PVCDP22083S
300	315	3 m	SN8	SWJ	41	265	6	PVCDP30083S

CIVILPIPES PTY LTD

ABN 30 168 566 667
2 Potassium St. Narangba Qld 4504
PO Box 304, North Lakes Qld 4509



Web:
civilpipes.com.au



Telephone:
+61 7 3053 3456



E-mail:
sales@civilpipes.com.au

