

FEATURES

- Full bore for optimal flow performance with minimal head loss
- Specially compounded nitrile seals designed to exceed valve life
- All plastic design for maximum corrosion resistance
- Integral Purge/Bypass ports for compact and reliable connections
- Open and Close indicators
- Precision manufacturing processes ensure lower operating torques
- ISO 9001 certified manufacturing facility
- Each valve includes a Traceability label



PE Ball Valve with Purge/Bypass connection points

TECHNICAL DATA

Standards:	EN 1555-4, EN 122201-4	
Size Range:	DN 20 – DN 400	Standard 1/4 Turn
	DN 160 – DN400	Gearbox Option 2 ½ Turn
Pressure Rating:	PE100, SDR 11 GAS, WATER PN 16	
Materials:	Polyethylene Body Polypropylene Ball Nitrile Seat and Seals	
Spigot Ends:	Suitable for butt welding and electrofusion welding	
Options:	Stem Extension Gearbox 2 ½ Turn – Short type or Extended type Purge Extensions – Single or Double Bypass Valve arrangement	



PE Ball Valve with Extended Gearbox



PE Ball Valve with Gearbox (Short) and Bypass Valve arrangement

CIVILPIPES PTY LTD

ABN 30 168 566 667
2 Potassium St. Narangba Qld 4504
PO Box 304, North Lakes Qld 4509



Web:
civilpipes.com.au



Telephone:
+61 7 3053 3456



E-mail:
sales@civilpipes.com.au

